

TPD-02

© HALE electronic GmbH / Salzburg, Austria
TECHNICAL MANUAL

Author: 55, 60

28.8 - Technical data

Page 1
07.03.2018

TECHNICAL DATA TPD-02

Operating voltage:

6-18 V

Nominal voltage:

12 V

protected against wrong polarity

Consumption:

180 mA, max. 1,5A

sleep: 4mA

Printing unit:

graphics capable, incl. QR code

384 dots/line, up to 8cm/sec, 203 dpi

paper width 58 mm

28 characters / line

Interfaces:

- HALE CAN (mirror taximeter SPT-03, SPT-02, SPT-01, Microtax-06), CiA compatible

- RS 232 +/-12V

- Serial 5V interface

- 1200-76800 baud

- USB for software updates

Optional:

- Bluetooth

Special features:

Optimal printing quality through compensation of ambient temperature

Protection of the printer head

End of paper detection

Autosleep and wakeup

Easy Paper Load

Further features:

- 4coloured LED display

green - ready for printing

green blinking - active print-job/HALE-channel open

green/blue blinking - pairing mode

red - end of paper

- 2 keys, backlit

red/blue blinking - warm-up

red/yellow blinking - cool-down

red/green blinking - watchdog-reset

no light - standby/powerfail

Temperature range:

Operation: -10°C - +70°C

Stock: -25°C - +85°C

Dimensions:

110 x 81 x 44 mm

Weight:

180 g 220 g incl. paper roll